Installation

The service can be installed through the Portainer web interface.

> Learn about creating a new stack.

Docker Compose

Use the following code to install the service:

```
---
services:
  amule:
    image: ngosang/amule
    container_name: amule
    environment:
      - PUID=1000
      - PGID=1000
      - TZ=America/Vancouver
      - GUI_PWD=
      - WEBUI_PWD=
      - MOD_AUTO_RESTART_ENABLED=true
      - MOD_AUTO_RESTART_CRON=0 6 * * *
      - MOD_AUTO_SHARE_ENABLED=false
      - MOD_AUTO_SHARE_DIRECTORIES=/incoming
      - MOD_FIX_KAD_GRAPH_ENABLED=true
      - MOD_FIX_KAD_BOOTSTRAP_ENABLED=true
    ports:
      - "4711:4711"
      - "4712:4712"
      - "4662:4662"
      - "4665:4665/udp"
      - "4672:4672/udp"
    volumes:
      # Persistent Data
```

```
      - /srv/amule:/home/amule/.aMule


      # Download Folders
      - /mnt/downloads/incoming:/incoming
      - /mnt/downloads/temp:/temp
    restart: unless-stopped
```

Revision #2
Created 9 March 2025 07:15:23 by metaphorraccoon
Updated 9 March 2025 07:38:05 by metaphorraccoon