Installation

The service can be installed through the Portainer web interface.

> Learn about creating a new stack.

Docker Compose

Use the following code to install the service:

```
---
services:
  app:
    image: monica:apache
    depends_on:
      - db
    ports:
      - 9011:80
    environment:
      - DB_HOST=db
      - DB_USERNAME=${DB_USER}
      - DB_PASSWORD=${DB_PASS}
      - APP_URL=${APP_URL}
      - APP_KEY=${APP_KEY}
    volumes:
      # Persistent Data
      - /srv/monica/config:/var/www/html/storage
    restart: unless-stopped

  db:
    image: lscr.io/linuxserver/mariadb:11
    environment:
      - MYSQL_RANDOM_ROOT_PASSWORD=true
```

```
      - MYSQL_DATABASE=monica
      - MYSQL_USER=${DB_USER}
      - MYSQL_PASSWORD=${DB_PASS}
    volumes:
      - /srv/monica/db:/var/lib/mysql
    restart: unless-stopped
```

Environment

Use the following environment to configure the service using the values prepared earlier:

```
DB_USER=
DB_PASS=
APP_URL=monica.example.com
APP_KEY=
```

Revision #4
Created 17 March 2025 20:29:26 by metaphorraccoon
Updated 17 March 2025 23:46:00 by metaphorraccoon