

Installation

The service can be installed through the Portainer web interface.

Learn about [creating a new stack](#).

Docker Compose

Use the following code to install the service:

```
---
services:
  db:
    image: mariadb:10.6.4-focal
    command: '--default-authentication-plugin=mysql_native_password'
    volumes:
      - /srv/wordpress/db:/var/lib/mysql
    restart: always
    environment:
      - MYSQL_ROOT_PASSWORD=
      - MYSQL_DATABASE=wordpress
      - MYSQL_USER=${DB_USER}
      - MYSQL_PASSWORD=${DB_PASSWORD}
    expose:
      - 3306

  wordpress:
    image: wordpress:latest
    ports:
      - 8080:80
    restart: always
    depends_on:
      - db
    volumes:
```

```
- /srv/wordpress/html:/var/www/html
```

```
environment:
```

- WORDPRESS_DB_HOST=db
- WORDPRESS_DB_USER=\${DB_USER}
- WORDPRESS_DB_PASSWORD=\${DB_PASSWORD}
- WORDPRESS_DB_NAME=wordpress

Environment

Use the following environment to configure the service using the values prepared earlier:

```
# Database Configuration
DB_USER=wordpress_admin

# Passwords
# After the initial setup, the passwords should be saved elsewhere and stack should be re-
# deployed with these settings deleted.

# Database Passwords
DB_PASSWORD=
```

Revision #5

Created 5 March 2025 05:03:18 by metaphorraccoon

Updated 9 March 2025 01:41:18 by metaphorraccoon